

Amendments to the Claims

This listing of the claims will replace all prior versions and listings of the claims in this patent application:

Listing of Claims:

Claims 1-241 (canceled)

242. (previously presented) A method for fabricating a chip package, comprising:
joining a die and a substrate, wherein said die has a top surface at a horizontal level,
wherein said die and said substrate are under said horizontal level;

after said joining said die and said substrate, forming a patterned circuit layer over said
horizontal level, wherein said patterned circuit layer extends across an edge of said die;

after said joining said die and said substrate, forming a passive device over said substrate
and over said horizontal level, wherein said passive device comprises a part not directly over any
die in said chip package; and

after said forming said patterned circuit layer and said forming said passive device,
separating said substrate into multiple portions.

243. (previously presented) A method for fabricating a chip package, comprising:
providing a first die having a top surface at a horizontal level, a second die having a top
surface at said horizontal level, and a separating material between said first and second dies,
wherein said separating material separates said first die from said second die;

after said providing said first and second dies and said separating material, forming a
passive device over said horizontal level, wherein said passive device has a first terminal
connected to said first die; and

after said forming said passive device, forming a metal bump over said horizontal level,
wherein said metal bump is connected to a second terminal of said passive device.

244. (previously presented) A method for fabricating a chip package, comprising:
providing a first die having a top surface at a horizontal level, a second die having a top surface at said horizontal level, and a separating material between said first and second dies, wherein said separating material separates said first die from said second die;
after said providing said first and second dies and said separating material, forming a passive device over said horizontal level, wherein said passive device has a part not directly over any die in said chip package;
after said forming said passive device over said horizontal level, forming an insulating layer on said passive device and over said horizontal level; and
after said providing said first and second dies and said separating material, forming a patterned circuit layer over said horizontal level, wherein said patterned circuit layer extends across an edge of said first die.

245. (previously presented) The method of claim 242, wherein said substrate comprises a metal substrate.

246. (previously presented) The method of claim 242 further comprising joining a film and said substrate, wherein an opening in said film exposes said substrate, followed by said joining said die and said substrate, wherein said die is in said opening.

247. (previously presented) The method of claim 246, wherein forming said opening in said film comprises a punching process.

248. (previously presented) The method of claim 246, wherein said film comprises a metal layer.

249. (canceled)

250. (previously presented) The method of claim 242, wherein said forming said patterned circuit layer comprises an electroplating process.

251. (withdrawn) The method of claim 242, wherein said forming said patterned circuit layer comprises a sputtering process.

252. (previously presented) The method of claim 242, wherein said forming said passive device comprises an electroplating process.

253. (withdrawn) The method of claim 242, wherein said forming said passive device comprises a sputtering process.

254. (previously presented) The method of claim 242, after said joining said die and said substrate, further comprising forming a solder bump over said horizontal level, followed by said separating said substrate.

255. (withdrawn) The method of claim 242, after said joining said die and said substrate, further comprising forming a gold bump over said horizontal level, followed by said separating said substrate.

256. (withdrawn) The method of claim 242, wherein said passive device comprises an inductor.

257. (previously presented) The method of claim 243 further comprising providing a substrate joined with said first and second dies, followed by said forming said passive device further over said substrate.

258. (previously presented) The method of claim 257, wherein said substrate comprises a metal substrate.

259. (previously presented) The method of claim 257, after said forming said metal bump, further comprising separating said substrate into multiple portions.

260. (withdrawn) The method of claim 243, wherein said separating material comprises an epoxy.

261. (previously presented) The method of claim 243, after said providing said first and second dies and said separating material, further comprising forming a patterned circuit layer over said horizontal level and over said separating material, wherein said patterned circuit layer extends across an edge of said first die, followed by said forming said metal bump.

262. (previously presented) The method of claim 261, wherein said forming said patterned circuit layer comprises an electroplating process.

263. (withdrawn) The method of claim 261, wherein said forming said patterned circuit layer comprises a sputtering process.

264. (previously presented) The method of claim 243, wherein said forming said passive device comprises an electroplating process.

265. (withdrawn) The method of claim 243, wherein said forming said passive device comprises a sputtering process.

266. (previously presented) The method of claim 243, wherein said forming said metal bump comprises forming a solder bump over said horizontal level, wherein said solder bump is connected to said second terminal.

267. (withdrawn) The method of claim 243, wherein said forming said metal bump comprises forming a gold bump over said horizontal level, wherein said gold bump is connected to said second terminal.

268. (withdrawn) The method of claim 243, wherein said passive device comprises an inductor.

269. (previously presented) The method of claim 244, wherein said forming said patterned circuit layer comprises an electroplating process.

270. (withdrawn) The method of claim 244, wherein said forming said patterned circuit layer comprises a sputtering process.

271. (previously presented) The method of claim 244, wherein said forming said passive device comprises an electroplating process.

272. (withdrawn) The method of claim 244, wherein said forming said passive device comprises a sputtering process.

273. (previously presented) The method of claim 244, after said forming said insulating layer and said forming said patterned circuit layer, further comprising forming a solder bump over said horizontal level.

274. (withdrawn) The method of claim 244, after said forming said insulating layer and said forming said patterned circuit layer, further comprising forming a gold bump over said horizontal level.

275. (withdrawn) The method of claim 244, wherein said passive device comprises an inductor.

276. (previously presented) The method of claim 244, wherein said passive device comprises a capacitor.

277. (withdrawn) The method of claim 244, wherein said passive device comprises a resistor.

278. (withdrawn) The method of claim 244, wherein said passive device comprises a filter.

279. (withdrawn) The method of claim 244, wherein said separating material comprises an epoxy.

280. (previously presented) The method of claim 244 further comprising providing a substrate joined with said first and second dies, followed by said forming said passive device further over said substrate, and said forming said patterned circuit layer further over said substrate.

281. (previously presented) The method of claim 280, wherein said substrate comprises a metal substrate.

282. (previously presented) The method of claim 280, after said forming said insulating layer and said forming said patterned circuit layer, further comprising separating said substrate into multiple portions.

283. (previously presented) The method of claim 242, wherein said passive device comprises a capacitor.

284. (withdrawn) The method of claim 242, wherein said passive device comprises a resistor.

285. (withdrawn) The method of claim 242, wherein said passive device comprises a filter.

286. (previously presented) The method of claim 243, wherein said passive device comprises a capacitor.

287. (withdrawn) The method of claim 243, wherein said passive device comprises a resistor.

288. (withdrawn) The method of claim 243, wherein said passive device comprises a filter.

289. (withdrawn) The method of claim 243, wherein said separating material comprises a polymer.

290. (withdrawn) The method of claim 244, wherein said separating material comprises a polymer.